

ZENER DIODES


FEATURES

- Low cost
- Small size
- Glass sealed

MECHANICAL DATA

- Case: SOD-80 glass case
- Terminals: solderable per MIL - STD - 202, method 208
- Polarity: color band denotes cathode
- Mounting position: any
- Weight: 0.05 grams

BZV55C2V0---BZV55C75



LL-34(SOD-80) Dimensions in millimeters

ABSOLUTE MAXIMUM RATINGS (TA=25 °C unless otherwise noted)

Parameter	Symbol	Value	Unit
Power Dissipation	P _{tot}	500 ¹⁾	mW
Junction Temperature	T _j	175	°C
Storage Temperature Range	T _s	- 55 to + 175	°C

1) Valid provided that leads are kept at ambient temperature at a distance of 8 mm from case

ELECTRICAL CHARACTERISTICS (Tamb=25 °C unless otherwise specified)

Parameter	Symbol	Max.	Unit
Thermal Resistance Junction to Ambient Air	R _{thA}	0.3 ¹⁾	K/mW
Forward Voltage at I _F = 100 mA	V _F	1	V

1) Valid provided that leads are kept at ambient temperature at a distance of 8 mm from case.

BZV55C2V0---BZV55C75

Type	Zener Voltage Range ¹⁾			Dynamic Resistance			Reverse Leakage Current			Temp. Coefficient of Zener Voltage
	VZ _{NOM}	V _Z	at I _{ZT}	Z _{ZT}	Z _{ZK}	at I _{ZK}	T _a = 25 °C	T _a = 125 °C	at V _R	
	(V)	(V)	(mA)	Max. (Ω)	Max. (Ω)	(mA)	Max. (μA)	Max. (μA)	(V)	
BZV55C2V0	2	1.8...2.15	5	85	600	1	100	200	1	-0.09...-0.06
BZV55C2V2	2.2	2.08...2.33	5	85	600	1	75	160	1	-0.09...-0.06
BZV55C2V4	2.4	2.28...2.56	5	85	600	1	50	100	1	-0.09...-0.06
BZV55C2V7	2.7	2.5...2.9	5	85	600	1	10	50	1	-0.09...-0.06
BZV55C3V0	3	2.8...3.2	5	85	600	1	4	40	1	-0.08...-0.05
BZV55C3V3	3.3	3.1...3.5	5	85	600	1	2	40	1	-0.08...-0.05
BZV55C3V6	3.6	3.4...3.8	5	85	600	1	2	40	1	-0.08...-0.05
BZV55C3V9	3.9	3.7...4.1	5	85	600	1	2	40	1	-0.08...-0.05
BZV55C4V3	4.3	4...4.6	5	75	600	1	1	20	1	-0.06...-0.03
BZV55C4V7	4.7	4.4...5	5	60	600	1	0.5	10	1	-0.05...+0.02
BZV55C5V1	5.1	4.8...5.4	5	35	550	1	0.1	2	1	-0.02...+0.02
BZV55C5V6	5.6	5.2...6	5	25	450	1	0.1	2	1	-0.05...+0.05
BZV55C6V2	6.2	5.8...6.6	5	10	200	1	0.1	2	2	0.03...0.06
BZV55C6V8	6.8	6.4...7.2	5	8	150	1	0.1	2	3	0.03...0.07
BZV55C7V5	7.5	7...7.9	5	7	50	1	0.1	2	5	0.03...0.07
BZV55C8V2	8.2	7.7...8.7	5	7	50	1	0.1	2	6.2	0.03...0.08
BZV55C9V1	9.1	8.5...9.6	5	10	50	1	0.1	2	6.8	0.03...0.09
BZV55C10	10	9.4...10.6	5	15	70	1	0.1	2	7.5	0.03...0.1
BZV55C11	11	10.4...11.6	5	20	70	1	0.1	2	8.2	0.03...0.11
BZV55C12	12	11.4...12.7	5	20	90	1	0.1	2	9.1	0.03...0.11
BZV55C13	13	12.4...14.1	5	26	110	1	0.1	2	10	0.03...0.11
BZV55C15	15	13.8...15.6	5	30	110	1	0.1	2	11	0.03...0.11
BZV55C16	16	15.3...17.1	5	40	170	1	0.1	2	12	0.03...0.11
BZV55C18	18	16.8...19.1	5	50	170	1	0.1	2	13	0.03...0.11
BZV55C20	20	18.8...21.2	5	55	220	1	0.1	2	15	0.03...0.11
BZV55C22	22	20.8...23.3	5	55	220	1	0.1	2	16	0.04...0.12
BZV55C24	24	22.8...25.6	5	80	220	1	0.1	2	18	0.04...0.12
BZV55C27	27	25.1...28.9	5	80	220	1	0.1	2	20	0.04...0.12
BZV55C30	30	28...32	5	80	220	1	0.1	2	22	0.04...0.12
BZV55C33	33	31...35	5	80	220	1	0.1	2	24	0.04...0.12
BZV55C36	36	34...38	5	80	220	1	0.1	2	27	0.04...0.12
BZV55C39	39	37...41	2.5	90	500	0.5	0.1	5	30	0.04...0.12
BZV55C43	43	40...46	2.5	90	500	0.5	0.1	5	33	0.04...0.12
BZV55C47	47	44...50	2.5	110	600	0.5	0.1	5	36	0.04...0.12
BZV55C51	51	48...54	2.5	125	700	0.5	0.1	10	39	0.04...0.12
BZV55C56	56	52...60	2.5	135	700	0.5	0.1	10	43	0.04...0.12
BZV55C62	62	58...66	2.5	150	1000	0.5	0.1	10	47	0.04...0.12
BZV55C68	68	64...72	2.5	200	1000	0.5	0.1	10	51	0.04...0.12
BZV55C75	75	70...79	2.5	250	1000	0.5	0.1	10	56	0.04...0.12

1) Tested with pulses tp = 20 ms.

2) The ZMM1 is a silicon diode with operation in forward direction. Hence, the index of all parameters should be "F" instead of "Z". Connect the cathode

BZV55C2V0--- BZV55C75

Typical Characteristics




FIG.2- POWER ,TEMPERATURE DERATING CURVE

