


## Compact, High Isolation Relay

- ROHS compliant.
- Compact single pole relay with high isolation between coil and contacts.
- Up to 10 A 250 VAC switching on the NO contacts.
- Ensures a withstand impulse voltage of 8,000 V between the coil and contacts.
- Low coil power consumption (SPST-NO: 200 mW, SPDT: 400 mW).
- UL class F coil insulation.
- UL, CSA and EN approvals.
- Ideal for appliance and HVAC controls.
- Tracking resistance: CTI > 250.



## Ordering Information

To Order: Select the part number and add the desired coil voltage rating (e.g. G5Q-14-EU-DC12)

Classification		Enclosure rating	Part number
Single contact, Class F coil	SPST-NO	Vented	G5Q-1A-EU
		Sealed	G5Q-1A4-EU
	SPDT	Vented	G5Q-1-EU
		Sealed	G5Q-14-EU

**Note:** When ordering, add the rated coil voltage to the model number.

Examples : G5Q 12VDC

Rated Coil Voltage

### Model Number Legend

G5Q-   -EU  VDC  
           1    2            3

#### 1. Number of Poles

1: 1 pole

#### 2. Contact Form

None: SPDT

A: SPST-NO

#### 3. Rated Coil Voltage

5, 12, 24VDC

## Specifications

### Coil Ratings

Rated voltage (V)		Rated current (mA)	Coil resistance (Ω)	Pick-up voltage	Drop-out Voltage	Maximum voltage	Power consumption (mW)
SPDT	DC5	80	63	75% of max.	5% of max.	190% at 23°C	400
	DC12	33.3	360				
	DC24	16.7	1440				
SPST-NO	DC5	40	125				200
	DC12	16.7	720				
	DC24	8.3	2880				

**Note:** Rated current and coil resistance are measured at 23°C with a tolerance of 10%.

## ■ Contact Ratings

Load	SPDT	SPST-NO
<b>Rated load (resistive)</b>	10A at 250 VAC (NO) 3A at 250 VAC (NO) 3A at 125 VAC (NO) 5A at 30 VDC (NO) 3A at 250 VAC (NC) 3A at 125 VAC (NC) 3A at 30 VDC (NC)	10A at 250 VAC 3A at 250 VAC 3A at 125 VAC 5A at 30 VDC
<b>Contact material</b>	AgNi	
<b>Rated carry current</b>	AC 10 A – DC 5A (NO)/ AC 3A – DC 3A (NC)	
<b>Max. switching voltage</b>	277 VAC, 30 VDC	
<b>Max. switching current</b>	AC: 10 A (NO)/3 A (NC) DC: 5 A (NO)/3 A (NC)	
<b>Max. switching capacity</b>	2500 VA, 150 W (NO) 750 VA, 90 W (NC)	
<b>Min. permissible load</b>	10 mA at 5 VDC (P level: $\lambda_{60} = 0.1 \times 10^{-6}$ operation)	

Note: P level:  $\lambda_{60} = 0.1 \times 10^{-6}$ /operation

## ■ Characteristics

<b>Contact resistance (see note 2)</b>	100 mΩ max.	
<b>Operate time</b>	10 ms max.	
<b>Release time</b>	5 ms max.	
<b>Insulation resistance (see note 3)</b>	1,000 MΩ min.	
<b>Dielectric strength</b>	4,000 VAC, 50/60 Hz for 1 min between coil and contacts 1,000 VAC, 50/60 Hz for 1 min between contacts of same polarity	
<b>Impulse withstand voltage</b>	8 kV (1.2 x 50 ms) between coil and contacts	
<b>Insulation Distance</b>	<b>Creepage (Typ)</b>	6.7 mm
	<b>Clearance (Typ)</b>	5.8 mm
<b>Tracking Resistance (CTI)</b>	250 V	
<b>Vibration resistance</b>	Destruction: 10 to 55 Hz, 1.5-mm double amplitude for 2 hours Malfunction: 10 to 55 Hz, 1.5-mm double amplitude for 5 minutes	
<b>Shock resistance</b>	Destruction: 1,000 m/s <sup>2</sup> (approx. 100G) Malfunction: 100 m/s <sup>2</sup> (approximately 10G)	
<b>Life expectancy (see note 4)</b>	Mechanical 10,000,000 operations (18,000 operations per hour)	
	Electrical 200,000 operations: 3 A (NO)/3 A (NC) at 125 VAC resistive load 100,000 operations: 3 A (NO)/3 A (NC) at 250 VAC 5 A (NO)/3 A (NC) at 30 VDC resistive load 25,000 operations: 10A (NO) at 250 VAC (900 operations per hour: 1 sec ON/3 sec OFF)	
	Switching frequency: 1,800 operations per hour: 1 sec ON/1 SEC OFF	
<b>Ambient temperature</b>	Operating: -40°C to 85°C (with no icing)	
<b>Ambient humidity</b>	Operating: 5% to 85%	

Note: 1. The data shown above are initial value.

2. The contact resistance is possible with 1 A applied at 5 VDC using a fall-of-potential method.

3. The insulation resistance is possible between coil and contacts and between contacts of the same polarity at 500 VDC.

4. The electrical life data items shown are possible at 23°C.

**■ UL508 (File No. E41515)**  
**CSA C22.2 No. 14 (File No. LR31928)**

Model	Coil ratings	Contact ratings	
		NO contacts	NO contacts
G5Q-EU	5-48 VDC	10 A, 250 VAC resistive 10 A, 30 VDC resistive 4 A, 120 VAC resistive, 100,000 ops. 4 FLA, 4 LRA 120 VAC, definite purpose, 100,000 operations.	3 A, 250 VAC resistive 3 A, 30 VDC resistive 4 LRA, 2 FLA, 120 VAC definite purpose, 100,000 operations.


**Note:** Ratings for both NO contacts and NC contacts are given at 105°C (221°F).

**EN 61810-1 (VDE Reg. no 125314)**


Model	Coil ratings	Contact ratings
G5Q-EU	5,12, 24 VDC	10 A, 250 VAC 5 A, 30 VDC (NO) 3 A, 250 VDC (NC)

## Engineering Data


**■ AMBIENT TEMPERATURE VS. MAXIMUM VOLTAGE**



**■ AMBIENT TEMPERATURE VS. RATED CARRY CURRENT**





**■ MAX. SWITCHING CAPACITY**




## Dimensions

**Note:** All units are in millimetres unless otherwise indicated.


### ■ G5Q-EU SPDT





PCB Mounting Holes  
(Bottom View)  
Tolerance:  $\pm 0.1$  mm




Terminal Arrangement/  
Internal Connections  
(Bottom View)




### ■ SPST-NO



PCB Mounting Holes  
(Bottom View)  
Tolerance:  $\pm 0.1$  mm



Terminal Arrangement/  
Internal Connections  
(Bottom View)



## Precautions



### CAUTION

Do not touch the terminals of the relay or the charted part of the socket when power is supplied to the Relay. Otherwise, an electric shock may occur.

**ALL DIMENSIONS SHOWN ARE IN MILLIMETRES.**

To convert millimetres into inches, multiply by 0.03937. To convert grams into ounces, multiply by 0.03527.